

DILOG

DC150

Digital Kabel TV mottagare med inbyggd Cryptoguard.

1000 kanaler
MPEG-2
RF in/ut
TV-scart
VCR-scart
RCA (CVBS UT, Audio L/R ut)
SPDIF optisk
RS-232
DVB och teletextning
Cryptoguard inbyggd
EPG : 7 dagar
Dynamisk hantering av NIT uppdatering
Teletext (VBI och OSD)
Mjukvara uppdatering via OTC
Aspect ratio : 4:3 full, 4:3 letter, 16:9
Sound track to selection audio language
8 x timer
8 x favoritlistor
Automatisk / manuell sökning



CryptoGuard

Dilog Nordic AB
Telefon: 031 28 88 30
E-mail: order@dilog.se
Hemsida: www.dilog.se

DILOG

Teknisk specifikation

EAN-number	7 350 021 771 506
Frequency range	50-860MHz
Demodulation	QAM 16,32,64,128,256
FEC rate	1/2,2/3,3/4,5/6,7/8
Profile level	MPEG-2 MP@ML
Transport stream	MPEG-2 ISO/IEC 13828-1
Video resolution	720x576 (PAL) 720x480 (NTSC)
Input bit rate (max)	81Mbits/s
Aspect ratio	4:3 , 16:9 , Letterbox
Audio decoding	MPEG / Musicam Layer I & II
Audio mode	Mono/Left/Right/Stereo
Conditional Access	Embedded Cryptoguard,Conax optional
Display	Display time and channel number
Audio output	TV-scart
TV scart	CVBS/RGB output
RCA	Video CVBS,RCA/Cinch volume & mute control 20bit dac, Max 2 Vrms, S/PDIF of Dolby digital bitstream out CVBS output,audio L/R output, CVBS input bypass
VCR scart	Audio L/R input bypass
Input voltage	90-250 (50/60HZ) V/AC
Power supply typ	SMPS
Power consumption	17W
Dimensions	340x60x265 mm
Weight	2.5 kg
Operating temperature	0-50c
Storage temperature	-20-60c

